

LEOTI, KANSAS

AL-9051 (FAA)

22195

WAAS CH 73043 W35A	APP CRS 355°	Rwy Idg TDZE Apt Elev	5100 3300 3303
--	------------------------	-----------------------------	---

APP CRS	Rwy Idg	5100
355°	TDZE	3300
	Apt Elev	3303

Rwy Idg	5100
TDZE	3300
Apt Elev	3303

RNAV (GPS) RWY 35

MARK HOARD MEML (3K7)

RNP APCH-GPS.

T	Baro-VNAV NA.
A NA	Use Syracuse altimeter setting.

MISSED APPROACH: Climb to 9000 direct OXTER and hold
continue climb-in-hold to 9000.

3K3 AWOS-3
119.975

DENVER CENTER
132.7 226.675UNICOM
122.7 (CTAF) **L**

△ 3955

MISSED APCH FIX

Diagram illustrating the YECUS system. A curved line represents a 30 NM radius. The angle between the vertical line and the arc is 175°. The angle between the horizontal line and the arc is 265°. A box labeled 9000 is shown. The text YECUS is also present.

(IAF) KEENA — 9000 NoPT — 085° —

9000 NoPT (IAF)
265° YECUS

ELEV 3303	D	TDZE 3300
-----------	----------	-----------

A diagram showing a 30° arc. At the top center of the arc is a diamond-shaped symbol with the text "FITAB" below it. Two horizontal arrows point outwards from the diamond, labeled "085°" on the left and "265°" on the right. Inside the arc, there is a rectangular box containing the number "9000". Below the arc, the text "30 NM" is written.

9000	OXTER
	

FITAB

7 NM
Holding Pattern

175° → 12000

← 355° 9000

CATEGORY		A	B	C	D
LPV	DA	3580-1	280 (300-1)		NA
LNNAV/ VNAV	DA	3630-1	330 (400-1)		NA
LNNAV	MDA	3680-1	380 (400-1)		NA

LEOTI, KANSAS

Orig 02DEC21

38°27'N-101°21'W

MARK HOARD MEML (3K7)

RNAV (GPS) RWY 35

NC-2, 22 FEB 2024 to 21 MAR 2024