

LOC I-RWS **APCH CRS** **Rwy Idg TDZE** **Arpt Elev**

111.5	010°	9318 261 280
--------------	-------------	---

AL-561 [USAF]

JOINT BASE ANDREWS (KADW)

RADAR or DME required.

ALSf-2

† MISSED APPROACH: Climbing to 2500, intercept ADW VORTAC R-009 to EGUDE and hold.

ATIS	POTOMAC APP CON	TOWER	GND CON	CLNC DEL	CPDLC
133.675 251.05	128.0 335.5	118.4 349.0	121.8 275.8	127.55 285.475	

541 CATEGORY II & III ILS SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

WASHINGTON
111.0 DCA
Chan 47

ANDREWS
113.1 ADW
Chan 78

BALTIMORE
115.1 BAL
Chan 98

FOWKS
ADW 5.9
RADAR

PREZZ
(IAF)
ADW 13
2500

EGUDE
ADW
R-009
13

LOCALIZER 111.5
I-RWS

HOLD 2500
RADAR required for holding above 4000 or > 230 KIAS

HOLD 2500
RADAR required for holding above 4000 or > 230 KIAS

MSA ADW 2.5 NM
2200

EMERG SAFE ALT 100 NM 6200

CATEGORY	A	B	C	D	E
S-ILS 1L	CAT II RA 108/12 100 DA 361				
S-ILS 1L	CAT IIIa RVR 07				
S-ILS 1L	CAT IIIb RVR 06				
S-ILS 1L	CAT IIIc NA				

VORTAC

GS 3.00° TCH 55

TDZL/CL
Rwy 1L-19R
HIRL all rws

ELEV 280 **TDZE 261**

306 **861** **761** **483** **381** **381** **381**

9318 x 200 **9756 x 150** **0.3% UP**

TWR

1L **1R**