

23334

INDIANAPOLIS INTL (IND)
INDIANAPOLIS, INDIANA

**TOP ALTITUDE:
ASSIGNED BY
ATC**

LOCALIZER
111.15 I-FVJ 
Chan 48(Y)

HOOSIER
110.2 OOM 
Chan 39

FOOT RADAR

DAWNN
10000
DUISVILLE Transition)

LOUISVILLE
114.8 IU ::
Chan 95

MYSTIC
108.2 MYS

Rwys 5L/R, 14, 23L/R, 32: Standard.

NOTE: Assigned to aircraft with a requested altitude of 11 000 or above.

NOTE: Chart not to scale.

07DEC17

INDIANAPOLIS, INDIANA
INDIANAPOLIS INTL (IND)

EC-2, 22 FEB 2024 to 21 MAR 2024



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 23R (TURBOJETS ONLY-DME REQUIRED): Climb on heading 230° to I-UZK 2.6 DME, then on assigned heading 230° or 215° to assigned altitude.

Thence....

TAKEOFF RWY 23L (TURBOJETS ONLY-DME REQUIRED): Climb on heading 230° to I-FVJ 2.3 DME, then on assigned heading 210°, 230°, or 245° to assigned altitude.

Thence....

TAKEOFF RWY 5R (TURBOJETS ONLY-DME REQUIRED): Climb on heading 050° to I-OQV 0.3 DME, then on assigned heading 050° or 070° to assigned altitude.

Thence....

TAKEOFF ALL OTHER RWYS (TURBOJETS ONLY): Climb on assigned heading to assigned altitude. Thence....

TAKEOFF ALL RWYS (PROPELLER ONLY): Climb on assigned heading to assigned altitude. Thence....

DEPARTING ALL OTHER AUTHORIZED RUNWAYS/AIRPORTS: Climb on assigned heading to assigned altitude. Thence....

....on RADAR vectors to join VHP R-174 to DAWNN INT then on transition or assigned route. Expect clearance to requested altitude ten minutes after departure.

LOUISVILLE TRANSITION (DAWNN1.IIU): From over DAWNN INT on IIU R-311 to IIU VORTAC.

MYSTIC TRANSITION (DAWNN1.MYS): From over DAWNN INT on MYS R-002 to MYS VOR.