


CANNON AFB (KCVS)



LOC HOVI 110.35	APCH CRS 128°	Rwy Idg TDLE Arpt Elev 8186 4294 4295	AL-512 [USAF]	CANNON AFB (KCVS)
A/C RADAR or DME required.			SSAIR	T MISSED APPROACH: Climb to 6000 on CVS TACAN R-130 5.6 DME (HOMER) then climbing right turn to 7000 intercept CVS R-193 to 112 DME (CLINK) and hold.
▼ * When ALS inop, increase vis to 3 mi.			(A3) 	
ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLINIC DEL 120.2 293.225

**** When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1 3/8 miles.**

† Missed approach requires use of RNAV or ATC radar monitoring.



EMERG SAFE ALT 100 NM 8000



		4.9 NM						
CATEGORY	A	B	C	D	E			
SILLS 13 *	4544-1/2 250 (300-1/2)							
S-LOC 13 **	4760-1/2 466 (500-1/2)							
C CIRCLING	480-1	4860-1/2	5000-2/4	5020-2/2	555(600-1/2)	705(800-2/4)	725(800-2/2)	
	545 (600-1)	Mn:Sec	4:54	3:16	2:27	1:58	1:38	

3.1

A3

FAF to MAP 4.9 NM

HIRL all nws

CLOVIS, NEW MEXICO

34° 23' N-103° 19' W

CANNON AFB (KCVS)

Amdt 4 30JAN20

ILS or LOC RWY 13

CANNON AFB (KCVS)


LOC I-BNN 108.3	APCH CRS 308°	Rwy Idg TDZE Apt Elev 8196 4270 4295
---------------------------	-------------------------	--

A/C RADAR or DME required.

▼ * When A/S inop, increase vis to $\frac{3}{4}$ mile.

**** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 1/8 miles.**

[†]Missed approach requires use of RNAV or ATC radar monitoring.

[illegible]


34°23'N-103°19'W

CLOVIS, NEW MEX
Amdt 4 16AUG18

ILS or LOC RWY 31

ILS or LOC Rwy 4

CANNON AFB (KCVS)




APCH CRS	Rwy Idg	8196
128°	TDZE	4294
	Arprt Elev	4295

AL-512 (USAF)

CANNON AFB (KCVS)

RNP APCH	SSALR	MISSED APPROACH: Climb to 7000 direct HOMEP, then track 128° to SOPLE and hold.
▼ * When ALS inop increase vis to 1 3/8 miles. ** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 1/2 miles.	A3	

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
---------------------	---------------------------------	-----------------------	------------------------	---------------------------



RAPKE		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 37).		7000	HOMEP	tr 128°	SOPLE	ELEV 4295	TDZE 4294
7000		128°		LERAY	1.5 NM to RW13		RW13		
GP 3.04° TCH 45		5900		4.8 NM					
CATEGORY	A	B	C	D	E				
LNAV/VNAV DA*	4766-1		472		(500-1)				
LNAV MDA**	4820-½ 526 (600-½)		4820-1		526 (600-1)				
CIRCLING	4840-1 545 (600-1)		4860-1½ 565 (600-1½)		5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)			

CLOVIS, NEW MEXICO

RNAV (GPS) RWY 22

WAAS CH 41173 W22A	APCH CRS 218°	Rwy Idg 10,003 TDZE 4295 Arpt Elev 4295
--------------------------	------------------	---

AL-512 (USAF)

CANNON AFB (KCVS)

T * When ALS inop, increase RVR to 40, vis to 3/4 mile. ** When ALS inop, increase vis to 1 1/4 miles. *** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/4 miles.	ALSF-1 	MISSED APPROACH: Climb to 7000 direct JEBES, track 171° to CLINK and hold.
---	--	--

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
---------------------	---------------------------------	-----------------------	------------------------	---------------------------


4866

For uncompensated
Baro-VNAV systems,
Procedure NA below -23°C
(-9°F) or above 54°C (130°F).


DME/DME RNP-0.3 NA

CAUTION: Group
4 WCH 19ft.


Missed approach
requires use of RNAV or
ATC RADAR monitoring.



EMERG SAFE ALT 100 NM 9000



CATEGORY	A	B	C	D	E
LPV DA*	4495/24		200	(200-½)	
LNAV/VNAV DA**	4720/40		425	(500-¾)	
LNAV MDA***	4720/24	425 (500-½)	4720/40	425	(500-¾)
 CIRCLING	4840-1	545 (600-1)	4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)



CLOVIS, NEW MEXICO

34°23'N - 103°19'W

CANNON AFB (KCVS)

Amdt 6 16JUL20

RNAV (GPS) RWY 22

SW-1, 22 FEB 2024 to 21 MAR 2024

SW-1, 22 FEB 2024 to 21 MAR 2024

RNAV (GPS) RWY 4

WAAS CH 41172 W04A	APCH CRS 038°	Rwy Idg TDZE Arpt Elev	10,003 4284 4295
--------------------------	------------------	------------------------------	------------------------

AL-512 (USAF)


CANNON AFB (KCVS)

⚠ * When ALS inop, increase RVR to 40, vis to 3/4 mile.
** When ALS inop increase RVR to 60 vis to 1 1/8 miles.
*** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
CAT CDE RVR to 60, vis to 1 1/8 miles.

ALS-1

MISSED APPROACH: Climb to 7000 direct FETEP, then track to HEKDI and hold.

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
---------------------	---------------------------------	-----------------------	------------------------	---------------------------



5 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI angle 2.50/TCH 41°).

7000 FETEP

ELEV 4295

TDZE 4284

CATEGORY	A	B	C	D	E
LPV DA*	4484/24	200	(200-1/2)		
LNAV/VNAV DA**	4700/40	416	(500-3/4)		
LNAV MDA***	4700/24 416 (500-1/2)	4700/40 416 (500-3/4)			
C CIRCLING	4840-1 545 (600-1)	4840-1 1/2 545 (600-1 1/2)	4980-2 1/4 685 (700-2 1/4)	5020-2 1/2 725 (800-2 1/2)	

HIRL all Rwys

RNAV (GPS) RWY 4


SW-1, 22 FEB 2024 to 21 MAR 2024

SW-1, 22 FEB 2024 to 21 MAR 2024

CANNON AFB (KCVS)

TACAN Chen 53	APCH CRS 120°	Rwy, ldg 4294 TDLE 4295 Aptl Elev	8196	AL-512 [USAF]	CANNON AFB (KCVS)
▼ * When A15 inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.				SSAR (A3)	† MISSED APPROACH: Climb to 6000 over CVS TACAN R-130 to 5.6 DME (HOMER) then turn right climbing to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.
A115 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225	

SW-1, 22 FEB 2024 to 21 MAR 2024



EMERG SAFE ALT 100 NM 9000

EMERG SAFE ALT 100 NM 9000					ELEV 4295		TDZE 4294	
			6000 CVS R-130		HOMEP CVS R-130 (56)		7000 CLINK CVS R-193 (12)	
CATEGORY	A	B	C	D	E			
S-13 *	4800-3/4	506 (600-3/4)	4800-1	506 (600-1)				
CIRCLING	4840-1	545 (600-1)	4860-1 1/2	5000-2 1/4	5020-2 1/2			

HIRL all 'wvs

Diagram showing a flight path with a 120° turn, altitudes 4525, 4433, and 4421, and a 3.13° climb. The path is labeled with aircraft types and altitudes: MESBE R-300 (12), CEDAV (57), HASRU (27), and TACAN. The path ends at 6000.

Diagram showing a flight path with a 120° turn, altitudes 4525, 4433, and 4421, and a 3.13° climb. The path is labeled with aircraft types and altitudes: MESBE R-300 (12), CEDAV (57), HASRU (27), and TACAN. The path ends at 6000.


CLOVIS, NEW MEXICO
Amdt 2 09NOV17

34°23'N-103°19'W

CANNON AFB (KCVS)
TACAN RWY 13

TACAN RWY 22

CANNON AFB (KCVS)



TACAN RWY 22

CLOVIS, NEW MEXICO

TACAN RWY 31


TACAN CVS Chan 53	APCH CRS 316°	Rwy ldg TDZE Arprt Elev	8196 4270 4295
----------------------	------------------	-------------------------------	----------------------

AL-512 (USAF)

CANNON AFB (KCVS)

† * When ALS inop, increase CAT AB vis to 1 mile, CAT CDE increase vis to 1 3/8 miles.	SSALR A3	† MISSED APPROACH: Climb to 6000 out CVS TACAN R-306 to 5.5 DME (LERAY) then turn left climbing to 7000 intercept CVS TACAN R-193 to 12 DME (CLINK) and hold.
--	-------------	---

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
---------------------	---------------------------------	-----------------------	------------------------	---------------------------



6000 CVS R-306	LERAY CVS 5.5	7000 CVS R-193	CLINK CVS 12	TOLDE R-136 12	CLINK R-193 12	ELEV 4295 4525	TDZE 4270
CATEGORY	A	B	C	D	E		
S-31 *	4700-½ 430 (500-½)		4700-¾ 430 (500-¾)				
CIRCLING	4840-1 545 (600-1)		4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)		

CLOVIS, NEW MEXICO

34°23'N - 103°19'W

CANNON AFB (KCVS)

Amdt 3 10OCT19

TACAN RWY 31

SW-1, 22 FEB 2024 to 21 MAR 2024

SW-1, 22 FEB 2024 to 21 MAR 2024

CLOVIS, NEW MEXICO

TACAN RWY 4


TACAN CVS Chan 53	APCH CRS 048°	Rwy ldg TDZE Arpt Elev	10,003 4284 4295
----------------------	------------------	------------------------------	------------------------

AL-512 (USAF)

CANNON AFB (KCVS)

† * When ALS inop, increase CAT A8 RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1 1/8 miles.	ALSF-1 	† MISSED APPROACH: Climb to 6000 via CVS TACAN R-036 to 5.1 DME (FETEP), cross FETEP at or below 6000, then turn left climbing to 7000 to intercept CVS TACAN R-003 to 12 DME (HEDOB) and hold.
---	------------	---

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
---------------------	---------------------------------	-----------------------	------------------------	---------------------------



CLINK R-193 12		FERAK R-228 12		FESOG 6		FETEP CVS 5.1		7000 CVS R-003		HEDOB CVS 12		ELEV 4295	TDZE 4284
7000		6000		5800		6000		7000		ELEV 4295		TDZE 4284	
2.57°		048°		048°		048°		048°		ELEV 4295		TDZE 4284	
TCH 41		12 Arc		5.5 NM		5.5 NM		5.5 NM		ELEV 4295		TDZE 4284	
CATEGORY	A	B	C	D	E								
S-4*	4700/24	416 (500-½)	4700/40	416	(500-¾)								
CIRCLING	4840-1	545 (600-1)	4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)								

CLOVIS, NEW MEXICO

34°23'N - 103°19'W

CANNON AFB (KCVS)

Amdt 3 10OCT19

TACAN RWY 4

SW-1, 22 FEB 2024 to 21 MAR 2024

SW-1, 22 FEB 2024 to 21 MAR 2024