




HI-ILS Y or LOC Y RMY 14



RADAR or DME required.

MISSED APPROACH: CI right turn to 3000 on GP
GPT 13.3 DME and hold

DME from GPT VORTAC. Simultaneous reception of I-GPT and GPT DME required.



500	3000	MINNI
	 GPT R-193	



GULFPORT-BILOXI INTL (KGPT)

Amdt 7A 31DEC20

HI-ILS Y or LOC Y RWY 14

GULFPORT, MISSISSIPPI

HI-ILS Y or LOC Y RWY 32

LOC I-LUXI	APCH CRS	Rwy Idg	TDZE
108.3	317°	27	28
		Appt Elev	28

AL-576 [USAF]

GULFPORT-BILOXI INTL (KGPT)


⚠ * When ALS inop increase CAT E RVR 40. RVR 18 authorized with use of FD or AP or HUD to DA. **⚠** ** When ALS inop increase RVR 55.



MAISR
MISSED APPROACH: Climb to 2000 on GPT VORTAC R-313 to CAESA/GPT 17.4 DME and hold.


ATIS *	GULFPORT APP CON	GULFPORT TOWER *	GND CON	UNICOM	ASR
119.45	124.6 354.1 130°-309° 127.5 254.25 310°-129°	123.7 CTAF 0 339.8	120.4 348.6	122.95	

1549
A
Glide slope unusable when Twr closed. Only LOC MIN authorized during this period.
DME from GPT VORTAC. Simultaneous reception of I-LUXI and GPT DME required.



EMERG SAFE ALT 100 NM 3100

2000	CAESA	WGS1 and descent angles not coincident (WGS1 Angle 3.00/TCH 72).
GPT	17.4	
R-313		



CATEGORY	C	D	E
S-ILS 32 *	228/24	200	(200-1/2)
S-LOC 32 **	380/30	352	(400-3/4)
G CIRCLING	820-2 1/4 791 (800-2 3/4)	820-2 1/2 791 (800-2 1/2)	820-2 3/4 791 (800-2 3/4)

GULFPORT, MISSISSIPPI

GULFPORT-BILOXI INTL (KGPT)


Archt 1 07NOV19

HI-ILS Y or LOC Y RWY 32

AL-576 [USAF]

GULFPORT-BILOXI INTL (KGPT)

- * When ALS inop, increase RVR to 6000.
- ** When ALS inop, increase vis to 1 3/8 miles

REPORT TO

SC-4, 22 FEB 2024 to 21 MAR 2024

30° 24' N - 89° 04' W

GULFPORT-BILOXI INTL (KGPT)



HI-TACAN Y RWY 14

LOC I-GPT	APP CRS	Rwy Idg	9002
110.9	137°	TDZE	27
		Apt Elev	28

ILS Z RWY 14 (SA CAT II)
GULFPORT-BILOXI INTL (GPT)


Reduced lighting: requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown. Procedure NA when tower closed. MALSR <td> MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold. </td>	MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold.
---	---

ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
----------------	------------------------------------	--	------------------------	------------------



CATEGORY	A	B	C	D
S-ILS 14	CAT II RA 113/12 100 DA 127			

SA CATEGORY II ILS - SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED



LOC I-GPT	APP CRS	Rwy Idg	9002
110.9	137°	TDZE	27
		Apt Elev	28

ILS Z or LOC Z RWY 14
GULFPORT-BILOXI INTL (GPT)



For inop ALS, increase S-ILS 14 Cat E visibility to RVR 4000 and S-LOC 14 Cat E visibility to 1½ SM.
**RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR


MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold.

ATIS	GULFPORT APP CON ★	GULFPORT TOWER ★	GND CON	UNICOM
119.45	127.5 254.25	123.7 (CTAF) 0 339.8	120.4 348.6	122.95

Procedure NA for arrivals at CAESA on V552 westbound.



CATEGORY	A	B	C	D	E
S-ILS 14**	227/24 200 (200-½)				
S-LOC 14	560/24	533 (600-½)	560/55	533 (600-1)	
CIRCLING	560-1 532 (600-1)	640-1 612 (700-1)	820-2¼ 792 (800-2¼)	820-2½ 792 (800-2½)	820-2¾ 792 (800-2¾)



LOC I-UXI 108.3	APP CRS 317°	Rwy Idg TDZE Apt Elev	9002 27 28
---------------------------	------------------------	-----------------------------	---------------------------------------

ILS Z or LOC Z RWY 32
GULFPORT-BILOXI INTL (GPT)

DME or RADAR required, except DME required when control tower closed.

T Rwy 32 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to S-ILS 32. DME from GPT VORTAC. Simultaneous reception of I-UXI and GPT DME required. For inop ALS, increase S-LOC 32 all Cats visibility to RVR 5500.


MAISR




MISSED APPROACH: Climb to 500 then climbing left turn to 2000 on GPT VORTAC R-245 to MUDDA INT/GPT 12 DME and hold.

ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------

ALTERNATE MISSED
APCH FIX




ELEV	28		TDZE	27
------	----	--	------	----



500 ▲	2000 ↙	GPT	MUDDA	VICKR GPT 7	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).
----------	-----------	-----	-------	----------------	--

GS unusable when control tower closed.
Only localizer minimums authorized
during this period.



		0.9 NM		3.1 NM							
CATEGORY		A		B		C		D		E	
S-ILS 32		277/40		250 (300-¾)							
S-LOC 32		380/40		353 (400-¾)							
 CIRCLING		520-1 492 (500-1)	640-1 612 (700-1)	760-2 732 (800-2)		760-2¼ 732 (800-2¼)		760-2½ 732 (800-2½)			

21112

WAAS CH 97301 W14A	APP CRS 137°	Rwy Idg 9002 TDZE 27 Apt Elev 28
--	------------------------	---

RNAV (GPS) RWY 14
GULFPORT-BILOXI INTL (GPT)

RNP APCH.



T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or
A above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500.
ASR **RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR



MISSED APPROACH: Climb to 2800 direct IVOLE and hold.

ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



4 NM Holding Pattern

BROWA

6000 ← 317°
2800 137° →

GP 3.00°
TCH 50

AVYUM

2000

2000

*1.5 NM to RW14

RW14

*LNAV only.

CATEGORY	A	B	C	D
LPV DA**	227/24		200 (200-½)	
LNAV/VNAV DA	404/35		377 (400-¾)	
LNAV MDA	580/24 553 (600-½)		580/60 553 (600-1¼)	
CIRCLING	580-1 552 (600-1)	640-1 612 (700-1)	820-2¼ 792 (800-2¼)	820-2½ 792 (800-2½)

GULFPORT, MISSISSIPPI
Amdt 2A 31DEC20

30°24'N-89°04'W

GULFPORT-BILOXI INTL (GPT)
RNAV (GPS) RWY 14

SC-4, 22 FEB 2024 to 21 MAR 2024

WAAS CH 69512 W18A	APP CRS 182°	Rwy Idg 4935 TDZE 27 Apt Elev 28
--	------------------------	---




RNAV (GPS) RWY 18
GULFPORT-BILOXI INTL (GPT)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 54°C.

MISSED APPROACH: Climb to 2000 direct RUDAW and hold.

ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------




WAAS CH 56207 W32A	APP CRS 317°	Rwy Idg 9002 TDZE 27 Apt Elev 28
--	------------------------	---

RNAV (GPS) RWY 32
GULFPORT-BILOXI INTL (GPT)

RNP APCH-GPS. ▼ ▲ Rwy 32 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 54°C. For inop ALS, increase LNAV Cat A/B visibility to RVR 5500, and Cat C/D to RVR 6000.	MALSR AS	MISSED APPROACH: Climb to 2000 direct BROWA and hold.
--	-------------	--




ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



VORTAC GPT	APP CRS	Rwy Idg	9002
109.0	136°	TDZE	27
Chan 27		Apt Elev	29

VOR Y RWY 14
GULFPORT-BILOXI INTL (GPT)

ASR		MALSR	MISSED APPROACH: Climbing right turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold.	
ATIS 119.45	GULFPORT APP CON ★ 127.5 254.25	GULFPORT TOWER ★ 123.7 (CTAF) 0 339.8	GND CON 120.4 348.6	UNICOM 122.95



SC-4, 22 FEB 2024 to 21 MAR 2024

SC-4, 22 FEB 2024 to 21 MAR 2024



VORTAC GPT	APP CRS	Rwy Idg	9002
109.0	307°	TDZE	27
Chan 27		Apt Elev	28

VOR Z RWY 32

GULFPORT-BILOXI INTL (GPT)

DME required.	MALSR	MISSED APPROACH: Climb to 700 then climbing left turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold.
▼ ▲ Rwy 32 helicopter visibility reduction below RVR 4000 NA. For inop ALS, increase S-32 Cat A/B visibility to RVR 5500, and Cat C/D/E to RVR 6000.	AS AS	

ATIS	GULFPORT APP CON *	GULFPORT TOWER *	GND CON	UNICOM
119.45	127.5 254.25	123.7 (CTAF) 339.8	120.4 348.6	122.95



700	2000	GPT R-245	MUDDA	HOTIP GPT [6]	Remain within 15 NM
↑	↶		△		
		GPT [2]	CULAY GPT [0.9]	1700	127°
				307°	1700
				1700	307°
				3.04° TCH 47	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 72).
				1.1	4 NM
CATEGORY	A	B	C	D	E
S-32			440/40	413 (500-¾)	
CIRCLING	520-1 492 (500-1)	640-1 612 (700-1)	760-2 732 (800-2)	760-2¼ 732 (800-2¼)	760-2½ 732 (800-2½)

VOR Z or TACAN Z RWY 14
GULFPORT-BILOXI INTL (GPT)

MISSED APPROACH: Climbing right turn to 2000 on GPT VORTAC R-245 to MUDDA INT/12 DME and hold.



GND CON	UNICOM
120.4 348.6	122.95

UNICOM
122.95