

MONTGOMERY, ALABAMA

HI-TACAN-J

VORTAC MGMT	APCH CRS	Rwy Idg
112.1	133°	N/A
Chen 58	Appt Elev 221	


[USAF]

MONTGOMERY RGUL (DANNELLY FLD) (KMGM)

✚ Circling not authorized for CAT E north of Rwy 10-28.

MISSED APPROACH: Climb to 3500 direct MGM VORTAC and on MGM R-126 to SHADY/MGM 1.5 DME and hold.

ATIS ✚	APP CON	DANNELLY TOWER ✚	GND CON	CINC DEL	UNICOM	ASR
120.675	124.0 363.025	119.7 (C) 119.360.85	121.7 348.6	118.3 270.3	112.95	



CATEGORY	C	D	E
CIRCLING ✚	800-1½	860-2	860-2¼
	579 (600-1½)	639 (700-2)	639 (700-2¼)

MONTGOMERY, ALABAMA 32°18'N-86°24'W

MONTGOMERY RGUL (DANNELLY FLD) (KMGM)

Arndt 4C 25JAN24

HI-TACAN-J

ILS Y or LOC RWY 28
MONTGOMERY RGNL (DANNELLY FLD) (MGM)


MISSED APPROACH: Climb to 700 then climbing left turn to 3000 direct MGM VORTAC and hold, continue climb-in-hold to 3000 (TACAN aircraft continue climb to 3500 on MGM VORTAC R-126 to SHADY/MGM 15 DME and hold SE, RT, 306° inbound).

REIL Rwy 3 1

MIRL Rwy 3-21

HIRL Rwy 10-28

FAF to MAP 5.5 NM					
Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

700 ↑	3000 ↖	MGM 					
VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 75).							
CATEGORY	A		B		C	D	E
S-ILS 28	397-1/2				200 (200-1/2)		
S-LOC 28	700-1/2		503 (500-1/2)		700-1 503 (500-1)		
C CIRCLING	700-1		479 (500-1)		800-1 860-2 579 (600-1/2) 639 (700-2) 639 (700-2 1/4)		
WITBI FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)							
S-LOC 28	620-1/2		423 (400-1/2)		620-3/4 423 (400-3/4)		
C CIRCLING	700-1		479 (500-1)		800-1 860-2 579 (600-1/2) 639 (700-2) 639 (700-2 1/4)		



SE-4, 22 FEB 2024 to 21 MAR 2024

LOC I-DLV	APP CRS	Rwy Idg	9020
108.5	277°	TDZE	197
		Apt Elev	221

ILS Z RWY 28

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

NA GPS required. ASR For inop MALSR, increase S-ILS 28 Cat E visibility to ¾ mile.		MALSR	MISSED APPROACH: Climb to 3100 direct HEGAP and hold.		
ATIS	MONTGOMERY APP CON ★	DANNELLY TOWER ★	GND CON	CLNC DEL	UNICOM
120.675	124.0 363.025	119.7 (CTAF) 0 360.85	121.7 348.6	118.3 270.3	122.95



SE-4, 22 FEB 2024 to 21 MAR 2024

SE-4, 22 FEB 2024 to 21 MAR 2024

LOC I-MGM	APP CRS	Rwy Idg	9020
109.9	097°	TDZE	219
		Apt Elev	221

ILS Z or LOC Z RWY 10

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

RADAR or DME or ADF required.

▼

⚠



ASR

Circling NA for Cat E north of Rwy 10-28. For inop ALS, increase S-ILS 10** Cat E visibility to RVR 4000, and increase S-LOC 10 Cat E visibility to 1½ SM. **RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 700 then climbing right turn to 3000 direct MGM VORTAC and hold, continue climb-in-hold to 3000 (TACAN aircraft continue climb to 3500 on MGM VORTAC R-126 to SHADY/MGM 15 DME and hold SE, RT, 306° inbound).

ATIS	MONTGOMERY APP CON *	DANNELLY TOWER *	GND CON	CLNC DEL	UNICOM
120.675	124.0 363.025	119.7 (CTAF) 360.85	121.7 348.6	118.3 270.3	122.95



CATEGORY	A	B	C	D	E
S-ILS 10**	419/24 200 (200-½)				
S-LOC 10	660/24	441 (500-½)	660/45	441 (500-¾)	
CIRCLING	700-1	479 (500-1)	800-1½ 579 (600-1½)	860-2 639 (700-2)	860-2¼ 639 (700-2¼)

ELEV 221

TDZE 219

REIL Rwy 3

MIRL Rwy 3-21

HIRL Rwy 10-28

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

WAAS
CH **50100**
W10A


APP CRS
097°

Rwy Idg
TDZE
Apt Elev
9020
219
221

RNAV (GPS) RWY 10

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

RNP APCH.			MALSR		MISSED APPROACH: Climb to 2600 direct ICOTE and hold.
▼ ▲ ASR For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000; increase LNAV/VNAV Cat E visibility to RVR 5000; increase LNAV Cats C/D/E visibility to 1½ mile. Circling for Cat E NA north of Rwy 10-28. **RVR 1800 authorized with use of FD or AP or HUD to DA.					
ATIS 120.675	MONTGOMERY APP CON ★ 124.0 363.025	DANNELLY TOWER ★ 119.7 (CTAF) 0 360.85	GND CON 121.7 348.6	CLNC DEL 118.3 270.3	UNICOM 122.95



7 NM Holding Pattern

3100 ← 277°
097° →

GP 3.00°
TCH 50

HEGAP

2000

6.9 NM

GITEC

2000

3.9 NM

COVUS

1.5 NM to RWY 10

0.5 NM

RWY 10

1 NM

2600

ICOTE

*LNAV only.

*740

*1 NM to RWY 10

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 64).

CATEGORY	A	B	C	D	E
LPV DA **	419/24 200 (200-½)				
LNAV/VNAV DA	530/24 311 (400-½)				
LNAV MDA	600/24	381 (400-½)	600/35	381 (400-¾)	
CIRCLING	700-1	479 (500-1)	800-1½ 579 (600-1½)	860-2 639 (700-2)	860-2¼ 639 (700-2¼)

ELEV 221

TDZE 219

REIL Rwy 3 0

MIRL Rwy 3-21

HIRL Rwy 10-28

WAAS
CH **56200**
W28A

APP CRS
277°

Rwy Idg
TDZE
Apt Elev
9020
197
221

RNAV (GPS) RWY 28

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

▼


▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LPV Cat E visibility to ¾ mile; increase LNAV/VNAV Cat E visibility to 1¾ mile; increase LNAV Cat E visibility to 1½ mile. Circling for Cat E NA north of Rwy 10-28.

MALSR

MISSED APPROACH:
Climb to 3100 direct HEGAP and hold.

ATIS 120.675	MONTGOMERY APP CON ★ 124.0 363.025	DANNELLY TOWER ★ 119.7 (CTAF) 0 360.85	GND CON 121.7 348.6	CLNC DEL 118.3 270.3	UNICOM 122.95
------------------------	--	--	-------------------------------	--------------------------------	-------------------------



REIL Rwy 3 1
MIRL Rwy 3-21
HIRL Rwy 10-28

3100 ↑ HEGAP ✦	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).	7 NM Holding Pattern	ICOTE	097°→ ←277°	2600
* LNAV only		WITBI 1.5 NM to RW28	TEBOC 2000	277°	
* 1 NM to RW28	720*	2000	GP 3.00° TCH 56		
1 NM 0.5 4 NM 7 NM					
CATEGORY	A	B	C	D	E
LPV DA	397-½ 200 (200-½)				
LNAV/ VNAV DA	606-⅞ 409 (400-⅞)				
LNAV MDA	580-½ 383 (400-½)		580-⅝ 383 (400-⅝)		
CIRCLING	700-1 479 (500-1)		800-1½ 579 (600-1½)	860-2 639 (700-2)	860-2¼ 639 (700-2¼)

WAAS
CH **56633**
W03A

APP CRS
034°

Rwy Idg
TDZE **221**
Apt Elev **221**

RNAV (GPS) RWY 3

MONTGOMERY RGNL (DANNELLY FLD) (MGM)


▼

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 900 then climbing right turn to 3100 direct RUNOE and hold.

ATIS 120.675	MONTGOMERY APP CON ★ 124.0 363.025	DANNELLY TOWER ★ 119.7 (CTAF) 0 360.85	GND CON 121.7 348.6	CLNC DEL 118.3 270.3	UNICOM 122.95
------------------------	--	--	-------------------------------	--------------------------------	-------------------------



4 NM Holding Pattern

RUNOE

WINUT

ZUNRO 1.5 NM to RWY03

RWY03

3100

2000

*740

GP 3.00° TCH 43

7 NM

4 NM

1.5 NM

900

3100

RUNOE

* LNAV only

CATEGORY	A	B	C	D
LPV DA	484-7/8		263 (300-7/8)	
LNAV/VNAV DA	550-1 1/8		329 (400-1 1/8)	
LNAV MDA	620-1 399 (400-1)		620-1 1/8 399 (400-1 1/8)	
CIRCLING	700-1 479 (500-1)		800-1 1/2 579 (600-1 1/2) 860-2 639 (700-2)	

ELEV 221

TDZE 221

0.3% DOWN

9020 X 1.50

4011 X 1.50

TWR 368

REIL Rwy 3 0

MIRL Rwy 3-21

HIRL Rwy 10-28



034°

VORTAC	MGM	APP CRS	Rwy Idg	N/A
112.1		318°	TDZE	N/A
Chan 58			Apt Elev	221

VOR-A

MONTGOMERY RGNL (DANNELLY FLD) (MGM)

ATIS 120.675		MONTGOMERY APP CON ★ 124.0 363.025		DANNELLY TOWER ★ 119.7 (CTAF) 0 360.85		GND CON 121.7 348.6	CLNC DEL 118.3 270.3	UNICOM 122.95
-----------------	--	---------------------------------------	--	---	--	------------------------	-------------------------	------------------



CATEGORY		A	B	C	D
CIRCLING		760-1	539 (600-1)	800-1½ 579 (600-1½)	860-2 639 (700-2)

SE-4, 22 FEB 2024 to 21 MAR 2024

SE-4, 22 FEB 2024 to 21 MAR 2024