

LOC/DME I-LFT

109.5

Chan 32

APP CRS

216°

Rwy Idg

7659

TDZE

38

Apt Elev

42

ILS or LOC RWY 22L

LAFAYETTE RGNL/PAUL FOURNET FLD (LFTT)

VDP NA with Acadiana Rgnl altimeter setting. When local altimeter setting not received, use Acadiana Rgnl altimeter setting and increase DA to 267 feet; increase all MDA 40 feet and S-LOC 22L visibility Cat C/D to RVR 5000 and Circling visibility Cat C/D ¼ SM. For inop MALSR when using Acadiana Rgnl altimeter setting, increase S-LOC 22L Cat C and D visibility to 1½ mile.

**RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Acadiana Rgnl altimeter setting).

MALSR

A5

MISSED APPROACH:

Climb to 800 then climbing right turn to 2100 on LFT VORTAC R-264 to MICRO INT/ LFT 16 DME and hold.

ATIS	LAFAYETTE APP CON *	LAFAYETTE TOWER *	GND CON	CLNC DEL	UNICOM
134.05	121.1 363.0	118.5 (CTAF) 0 257.8	121.8	125.55	122.95

ALTERNATE MISSED APCH FIX

1242

Λ

Procedure NA for arrivals at BEDDY on V559 eastbound.

114.85 LLA

R-003

Chan 96(V)

MISSED APCH FIX

109.8 LFT

R-264

Chan 35

MICRO

LFT 16

548 Λ

230Λ

R-264

LOCALIZER 109.5

LFT

Chan 32

ELEV 42

TDZE 38

216°

22L

22R

4L

4R

11

29

5400 X 149

409 X 75

50 X 100

TWR 141

REIL Rwy 4L, 4R, 11, 22R and 29

MIRL Rwy 11-29 and 4L-22R

HIRL Rwy 4R-22L

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58

800

2100

MICRO

LFT R-264

*LOC only.

*H-LFT 2.6

I-LFT 1.4

LAFFS LOM

I-LFT 7.3

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50). Remain within 10 NM

036°

2100

216°

2000

GS 3.00°

TCH 54

CATEGORY	A	B	C	D
S-ILS 22L**	238/24	200 (200-½)		
S-LOC 22L	480/24	442 (500-½)	480/45	442 (500-¾)
	540-1	580-1	700-1¾	700-2
CIRCLING	498 (500-1)	538 (600-1)	658 (700-1¾)	658 (700-2)

LAFAYETTE, LOUISIANA

Amdt 5E 23APR20

LAFAYETTE RGNL/PAUL FOURNET FLD (LFTT)

30°12'N-91°59'W

ILS or LOC RWY 22L