

WAAS
CH **40304**
W09A

APP CRS
088°

Rwy Idg
TDZE **894**
Apt Elev **895**

RNAV (GPS) RWY 9

MENOMONIE MUNI/SCORE FLD (LUM)

RNP APCH.

▼

▲

Circling Rwy 18, 36 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MISSED APPROACH: Climb to 1400 then climbing right turn to 2800 direct GAGNR and hold.

AWOS-3 118.025	MINNEAPOLIS CENTER 125.3 335.6	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------

MSA RW09 25 NM
3200

Procedure NA for arrivals at BITLR
on V510 northwest bound and V413 westbound.

Procedure NA for arrivals at ELPAS
on V26 southwest bound.

Key Features:

- BITLR (IAF):** 2800 NoPT 087° (7.2), 4 NM to HATEL.
- HATEL (IF/IAF):** 2800 (6), 088° to ANILE.
- ANILE (FAF):** 2800, 088° to RW09.
- WIBAM:** 2.2 NM to RW09.
- RW09:** 1312, 987, 1099±.
- Altitudes:** 2180, 1775, 1688, 1385, 1078±, 1279, 1437.
- Hold:** 6000/2800, 268°/088°.
- ELPAS (IAF):** 2800 NoPT 044° (10.2).
- GAGNR:** 4 NM, 040°/220°.

4 NM Holding Pattern

1400

2800

GAGNR

HATEL

ANILE

WIBAM

6000

2800

GP 3.00°

TCH 48

268°

088°

088°

088°

2800

2800

1640

6 NM

3.6 NM

0.9

1.3

1.3 NM to RW09

1.3 NM to RW09

*1640

*1.3 NM to RW09

*LNAV only

81

3470 X 75

5074 X 75

36

27

ELEV	895	TDZE	894
------	-----	------	-----

CATEGORY	A	B	C	D
LPV DA	1144-3/4	250 (300-1)		NA
LNAV/VNAV DA	1423-1 1/2	529 (600-1 1/2)		NA
LNAV MDA	1360-1	466 (500-1)	1360-1 3/8 466 (500-1 3/8)	NA
CIRCLING	1420-1 525 (600-1)	1800-1 1/4 905 (1000-1 1/4)	1820-2 3/4 925 (1000-1 3/4)	NA

REIL Rwys 9 and 27 0

MIRL Rwys 9-27 and 18-36 0

MENOMONIE, WISCONSIN

MENOMONIE MUNI/SCORE FLD (LUM)

Amdt 1 20JUN19

44°54'N-91°52'W

RNAV (GPS) RWY 9