


WAAS CH 50236 W13A	APP CRS 126°	Rwy Idg TDZE Apt Elev	5007 975 975
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

MARSHALLTOWN MUNI (MTW)

RNP APCH.	⚠ Circling Rwy 18, 36 NA at night. Baro-VNAV and VDP NA when using Grinnell altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. ⚠ When local altimeter setting not received, use Grinnell altimeter setting and increase all DA 64 feet and all MDA 80 feet; increase LNAV Cats C/D and Circling Cat D visibility ¼ SM.	MISSED APPROACH: Climb to 2600 direct VUNDY and hold.
-----------	---	--

ASOS 128.325	WATERLOO APP CON ★ 120.9	CLNC DEL 120.9	UNICOM 122.8 (CTAF) 📻
------------------------	------------------------------------	--------------------------	---------------------------------



4 NM Holding Pattern		BRIDY		ATAXE		IKUDY 1.9 NM to RW13		*1620		*1 NM to RW13		RW13		VUNDY	
6000 2700		306° 126°		126°		2600		2600		2600		2600		2600	
GP 3.00° TCH 42															
		6 NM		3.1 NM		0.9		1 NM							
CATEGORY	A	B	C	D											
LPV DA	1225-1				250 (300-1)										
LNAV/VNAV DA	1225-1				250 (300-1)										
LNAV MDA	1320-1				345 (400-1)										
Ⓢ CIRCLING	1400-1 425 (500-1)		1440-1 465 (500-1)		1460-1½ 485 (500-1½)		1840-2¾ 865 (900-2¾)								

ELEV 975

TDZE 975

MIRL Rwys 13-31 and 18-36 📻
REIL Rwys 13 and 31 📻