

WAAS CH 61115 W28A	APP CRS 284°	Rwy Idg 8204 TDZE 5459 Apt Elev 5516
--	------------------------	---

RNAV (GPS) RWY 28

CENTRAL WYOMING RGNL (RIW)

RNP APCH - GPS.

⚠

Baro-VNAV and VDP NA when using Lander altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27°C or above 48°C. For inop MALSR, increase LNAV/VNAV all Cats visibility to ¾ mile and LNAV Cat C and D visibility to 1 mile. When local altimeter setting not received, use Lander altimeter setting: increase LPV DA to 5713 feet, LNAV/VNAV DA to 5763 and all visibilities ½ mile; increase all MDA 60 feet and LNAV Cat C and D visibility ½ mile. For inop MALSR, when using Lander altimeter setting, increase LPV all Cats visibility to ¾ mile and LNAV/VNAV all Cats visibility to 1 mile.

MALSR

MISSED APPROACH:

Climb to 7900 direct TIDHU and hold.

ASOS 121.425	SALT LAKE CENTER 133.25 285.6	UNICOM 122.8 (CTAF)
------------------------	---	-------------------------------

Procedure NA for arrival on RIW VOR/DME airway radials 072 CW 164.

Key features: TIDHU 5724, 104°/284°; RIVERTON RW 5679, 284°; FAF LIMNY 7700, 285°; DONVY 7700, 105°; Holding Pattern at DONVY (8600, 105°/285°); MSA 25 NM (11900); (IAF) HUNTZ 8600, 311°.

ELEV 5516		TDZE 5459
-----------	--	-----------

7900 TIDHU

LIMNY 7700

DONVY 7700

8600

GP 3.00°

TCH 50

CATEGORY	A	B	C	D
LPV DA	5659-½		200 (200-½)	
LNAV/VNAV DA	5709-½		250 (200-½)	
LNAV MDA	5820-½	361 (400-½)	5820-⅝	361 (400-⅝)
CIRCLING	6000-1	484 (500-1)	6000-1½ 484 (500-1½)	6120-2 604 (700-2)

RIVERTON, WYOMING
Amdt 1B 07SEP23

43°04'N-108°28'W

CENTRAL WYOMING RGNL (RIW)

RNAV (GPS) RWY 28

NW-1, 22 FEB 2024 to 21 MAR 2024

NW-1, 22 FEB 2024 to 21 MAR 2024