

LOC/DME I-SNA	APP CRS	Rwy Idg	5700
111.75	196°	TDZE	54
Chan 54(Y)		Apt Elev	56

ILS RWY 20R (SA CAT I)

JOHN WAYNE/ORANGE COUNTY (SNA)

Requires specific OPSPEC, MSPEC, or LOA approval.
Procedure NA when tower closed.

MALSR

MISSED APPROACH: Climb to 3000 on I-SNA
LOC south course (196°) to MINOE INT/I-SNA
10.9 DME.

D-ATIS	SOCAL APP CON	JOHN WAYNE TOWER ★	GND CON	CLNC DEL	CPDLC	UNICOM
126.0	121.3 263.1	126.8 (CTAF) 343.625	120.8	118.0		122.95

ALTERNATE MISSED APCH FIX

SEAL BEACH
SLI 115.7
Chan 104

Procedure NA for arrival
on SLI VORTAC airway
radials 058 CW 080.

SEAL BEACH
115.7 SLI
Chan 104

MISSED APCH FIX

113.6 LAX
R-123
Chan 83

MINOE
I-SNA 10.9

ELEV 56 TDZE 54

REIL Rwy 20L
MIRL Rwy 2R-20L
HIRL Rwy 2L-20R

1597±
1781±
4000
049°
(18.9)
R-060
R-068
R-076
561
196
323
425
540
1292
790
315
767±
396±
111.75
I-SNA
Chan 54(Y)
LOCALIZER
3000
I-SNA
S crs
(196°)
MINOE
VGSi and ILS glidepath not coincident
(VGSi Angle 3.00/TCH 68).
SNAKE INT
I-SNA 12.4
HUKEM INT
I-SNA 10
LEMON INT
I-SNA 7.8
SAGER INT
I-SNA 17.3
One Minute
Holding Pattern
016°→4500
←196°3500
GS 3.00°
TCH 51
887' 6.6 NM 2.2 NM 2.4 NM 4.9 NM
CATEGORY A B C D
S-ILS 20R RA 201/14 167 DA 221

SW-3, 22 FEB 2024 to 21 MAR 2024

SW-3, 22 FEB 2024 to 21 MAR 2024

SANTA ANA, CALIFORNIA

JOHN WAYNE/ORANGE COUNTY (SNA)

Amdt 14A 03NOV22

33°41'N-117°52'W

ILS RWY 20R (SA CAT I)