VALPARAISO, FLORIDA

ILS W or LOC W RWY 20

AL-436 [USAF] EGLIN AFB/DESTIN-FT WALTON BEACH (KVPS)

LOC/DME I-CAH	APCH CRS	Rwy ldg 10,001
109.1	192°	TDZE 63
Chan 28		Arpt Elev 84

DME, RADAR required for LOC approach.

* When ALS inop, increase RVR to 40 and vis to ¾ mile. When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
** CAT CDE RVR to 60 and vis to 1⅛ miles.

ALSF-1

MISSED APPROACH: Climb straight ahead to 3000 to CEW R-170/35 DME (MRCEE), then as directed by ATC.

ATIS *	APP CON	TOWER	GND CON	CLNC DEL
134.625 273.5	125.1 281.45 271°- 089° 132.1 360.6 090°- 270°	118.2 353.65	121.8 335.8	127.7 377.2

Procedure not usable at times due to restricted area activity.

R-286 286° 230K 106°
673
3000 108° (12.8)
012° R-012
(IAF) KANDE I-CAH 17
478 192° R-108 660
IAF CRESTVIEW 115.9 CEW Chan 106
356 CITEY I-CAH 13
466 367 2300 1700 NELVE I-CAH 9 378
229° HVVVR I-CAH 7 191
WARRINGTON Chan 2 DWG
339
LOCALIZER 109.1 I-CAH Chan 28
MRCEE CEW 35
R-170
MSA DWG 25 NM 1800

EMERG SAFE ALT 100 NM 3600

ELEV 84 TDZE 63

192° 20 175 12 179 203 157 255 164 202 193 243 TWR 30 2 11,987 x 300 10,001 x 300

HIRL all rwys
† Rwy 20 apch lgt 1500′ nonstandard.

3000 LOC DME WEGDU I-CAH 2.3 I-CAH 3.1 HVVVR I-CAH 7 NELVE I-CAH 9 CITEY I-CAH 13 R-012 KANDE I-CAH 17 CEW VORTAC
192° 2300 1700 192° 3000 192° 3000 108° 3000
GS 2.80° TCH 59
0.5 NM 4.7 NM

LOC FAF to MAP 4.7 NM					
Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34

CATEGORY	A	B	C	D	E
S-ILS 19 *	260/24		200	(200-½)	
S-LOC 19 **	480/24	420 (400-½)	480/40	420	(400-¾)
CIRCLING	660-1	576 (600-1)	760-2 676 (700-2)	760-2¼ 676 (700-2¼)	760-2½ 676 (700-2½)